

TECHNICAL INFO

The Core Collection

HEX XL HEXAGON BLENDS

ø 51,60 mm (2")

SUITABILITY AREA PRODUCT & COMPOSITION GUIDE

REFERENCE	WALL	FLOOR	WET AREAS	POOLS	MATERIAL
Hex XL Fosco Argent	Int/ Ext	Residential	Yes	Yes	Glass
Hex XL Fossil	Int/ Ext	No	Yes	Yes	Glass

TECHNICAL CHARACTERISTICS

TEST UNE-EN-ISO 10545-3 WATER ABSORPTION	TEST UNE-EN-ISO-101-92=101 SURFACE HARDNESS. MOHS.	TEST UNE-EN-ISO 10545-9 RESISTANCE TO THERMAL SHOCKS	TEST UNE-EN-ISO 10545-12 FROST RESISTANCE	TEST UNE-EN-ISO 10545-13:1998 RESISTANCE TO CHEMICAL ATTACK			
				DOMESTIC PRODUCTS	POOL WATER ADDITIVES	LOW ACID AND ALKALINS	HIGH ACID AND ALKALINS
None	4	Resistant	Resistant	GA	GA	GLA	GHA
TEST UNE-EN-ISO 10545-14 RESISTANCE TO STAINING	TEST UNE-EN-ISO 10545- 11=1997 CRACKING	DIN 51094 COLOUR STABILITY ON EXPOSURE TO LIGHT AND UV RAYS	DCOF WET DYNAMIC COEFFICIENT OF FRICTION ANSI A 137.1 STANDARD		DIN 51130:2004 SLIP RESISTANCE WEARING SHOES	DIN 51097 SLIP RESISTANCE IN BARE FEET	TEST UNE-ENV 12633:2003 (CTE) ANTI SKID COEFFICIENT, SUITABLE FOR OUTDOOR USE AND SWIMMING POOLS
Class 5	Resistant	Resistant	-		-	-	-

PACKING

SHEET HOJA	BOX CAJA	PALLET PALET	EURO PALLET EURO PALLET
Size / Dimensión: 286x284 mm (11.25"x11.18")	Sheets / Hojas: 6	Quantity / Cantidad: 88,20 m² (949.37 sqft)	Quantity / Cantidad: 58,80 m² (632.91 sqft)
Thickness / Espesor: 5,3 mm (0.173")	Quantity / Cantidad: 0,49 m² (5.27 sqft)	Boxes / Cajas: 180	Boxes / Cajas: 120
Weight / Peso: 0,921 Kg (2.03 lb)	Weight / Peso: 5,524 Kg (12.17 lb)	Gross weight / Peso bruto: 1014,32 Kg (2236 lb)	Gross weight / Peso bruto: 682,88 Kg (1505.49 lb)



Minimum
Order
1 module / 1 Box



Sales
Unit
Square meters



Mosaic
Support
MESH

All ONIX 98 % recycled glass mosaics series are made of molten glass. Molten glass characteristics may include irregular edges and small variations in size. These characteristics are inherent to the product and to the standard production. The small size and shape variations can affect the grout joint appearance and enhance the natural aspect of these products.

ONIX®